

# LM 928

LCD Panel	Driving system	TFT Color LCD
	Size	48.0cm(19.0")
	Pixel pitch	0.294mm( H ) x 0.294mm( V )
	Viewable angle	140° (H) 135° (V)
	Response time	8 ms ( Typical )
	Brightness	270 cd/m <sup>2</sup> (Typical)
	Contrast Ratio	550:1
Input	Video	R,G,B Analog Interface Digital Interface
	Separate Sync.	H/V TTL
	H-Frequency	30kHz – 83kHz (Analog)
	V-Frequency	55-75Hz (Analog)
Display Colors		16.0M Colours
Dot Clock		135MHz (Analog)
Max. Resolution		1280 x 1024 @75Hz(Analog)
Plug & Play		VESA DDC 2B™
EPA ENERGY STAR®	ON Mode	≤55W
	OFF Mode	≤2W
Input Connector		15-pin D-Sub DVI 24pin
Input Video Signal		Analog:0.7Vp-p(standard), 75 OHM, Positive Digital signal
Maximum Screen Size		Horizontal : 376.32mm; Vertical : 301.056mm
Power Source		100~240VAC,47~63Hz
Environmental Considerations		Operating Temp: 5° to 50°C Storage Temp.: -20° to 60°C Operating Humidity : 10% to 85%
Dimension		406x415x246 (W xHxD)mm
Weight (N. W.)		6.0kg Unit (net)
External Controls:	Switch	<ul style="list-style-type: none"> <li>• Auto Adjust Key</li> <li>• ▲ / Brightness</li> <li>• ▼ / Contrast</li> <li>• Power Button</li> <li>• MENU</li> </ul>
	Functions	<ul style="list-style-type: none"> <li>• Contrast</li> <li>• Brightness</li> <li>• Focus</li> <li>• Clock</li> <li>• H. Position</li> <li>• V. Position</li> <li>• (Warm)Color</li> <li>• (Cool)Color</li> <li>• RGB Color temperature</li> <li>• Input select</li> <li>• OSD Setup</li> <li>• Language</li> <li>• Information</li> <li>• Reset</li> <li>• Exit</li> </ul>
Power Consumption ( Maximum )		55 Watts
Regulatory Compliance		UL, CSA, TCO'99

Note: Specifications are subject to change without notice.

090606