



19" LCD Monitor 193S



TECHNICAL SPECIFICATIONS

Cabinet colour	Black / Silver
Screen Size	48.0cm (19.0")
Pixel pitch	0.294mm(H) × 0.294mm(V)
Maximum Screen Size	Horizontal : 376.32mm; Vertical : 301.056mm
Brightness	300 cd/m ² (Typical)
Contrast Ratio(typ)	700:1 (typ.)
Response time	5 ms (Typical)
Video	R,G,B Analog Interface Digital Interface
Separate Sync.	H/V TTL
H-Frequency	30kHz – 83kHz (Analog)
V-Frequency	55-75Hz (Analog)
Display Colors	16.0M Colours
Dot Clock	135MHz (Analog)
Max. Resolution	1280 × 1024 @75Hz(Analog)
Recommended Resolution	1280 x 1024 @60Hz
Resolution Supported	640 x 480 @60Hz/72Hz/75Hz ; 800 x 600 @56Hz/60Hz/72Hz/75Hz 1024 x 768 @60Hz/70Hz/75Hz ; 1280 x 1024 @60Hz/75Hz
Plug & Play	VESA DDC 2BTM
Input Connector	15-pin D-Sub DVI 24pin
Input Video Signal	Analog:0.7Vp-p(standard), 75 OHM, Positive Digital signal
HDCP Compatible	No
Power Source	100~240VAC,47~63Hz
Power Consumption	55 Watts (Max.)
Environmental	Operating Temp: 5° to 50°C ; Storage Temp.: -20° to 60°C
Considerations	Operating Humidity : 10% to 85%
User Control	Auto Adjust Key, ▲ / Brightness, ▼ / Contrast, Power Button, MENU
OSD Function	Contrast, Brightness, Focus, Clock, H. Position, V. Position, (Warm) Color, (Cool) Color, RGB Color temperature, Input select, OSD Setup, Language, Information, Reset, Exit
Speaker	No
Regulatory Compliance	EPA ENERGY STAR®, CE, UL, CSA, TCO99
Weight (N. W.)	6.0kg Unit (net)

Note: Specifications are subject to change without notice.
*Wall mount arm & bracket not included.

08/07

AOC®

Ultra-Thin LCD