



MULTI-FUNCTION 19" Widescreen LCD 198Fw



TECHNICAL SPECIFICATIONS

Cabinet colour	Titanium & Golden
Viewable Image Size	481mm
Pixel / Dot Pitch	0.285mm(H) × 0.285mm(V)
Display Area	Horizontal : 408mm ; Vertical : 255mm
Brightness (typ)	300cd/m ² (typ.)
Contrast Ratio(typ)	700:1 (typ.)
Response Time (typ)	5ms (typ.)
Viewing Angle H / V	150° /140°
Scanning Frequency	Horizontal: 30 - 83KHz; Vertical:55Hz - 75Hz
Pixel Frequency	135MHz
Maximum Resolution	1440 × 900 @60Hz
Recommended Resolution	1440 × 900 @60Hz
Resolution Supported	640 x 480 @60Hz/72Hz/75Hz ; 800 x 600 @56Hz/60Hz/72Hz/75Hz 1024 x 768 @60Hz/70Hz/75Hz ; 1280 x 1024 @60Hz/75Hz 1440 x 900 @60Hz
Display Colours	16.2M
Input Signal	DVI-I, S-Video, Composite, Component
Digital Input	DVI-I
HDCP Compatible	No
Connectors	29pin DVI-I ; S-Video ; CVBS; YPbPr
Power Source	110~240VAC, 50/60Hz Power Adapter Output 12VDC 4.5A
Power Consumption	65W (max.)
Plug & Play	DDC 1/2B
User Control	SOURCE, AUTO, POWER, VOL - , VOL+, MENU
OSD Function	Contrast, Brightness, Focus, Clock, H. Position, V. Position, Input Select, Language, Information, OSD Setup, (Warm)Colour, (Cool)Colour, sRGB, Colour temperature, Reset, Exit
OSD Languages	English, Spanish, French, Portuguese, German, Russian, Italian, Simple Chinese
Speaker	3W x 2
Regulations	cULus, FCC, CE, MPRII
Mechanical Features	VESA 100mm Wall Mountable*
Special features	PIP (video over graphic) ; 4 USB 2.0 ports
Dimensions(Monitor)	467 * 400* 105 mm
Dimensions(Carton)	570 * 520 * 185 mm
Weight(Net/Gross)	6Kg / 9Kg

Note: Specifications are subject to change without notice.

*Wall mount arm & bracket not included.

08/07

widescreen