



MULTI-FUNCTION 22" Widescreen LCD 2212Ph



TECHNICAL SPECIFICATIONS

Cabinet colour	Black
Viewable Image Size	558mm
Pixel / Dot Pitch	0.282mmx0.282mm
Display Area	474mmx296mm
Brightness (typ)	300 cd/m ²
Contrast Ratio(typ)	2000:1 (DCR)
Response Time (typ)	5ms
Viewing Angle H / V	CR=10: 170/160
Scanning Frequency	Horizontal: 30K~83KHz ; Vertical: 55~75 Hz
Pixel Frequency	160 MHz
Maximum Resolution	1680x1050@60Hz
Recommended Resolution	1680x1050@60Hz
Resolution Supported	For PC Mode- 640x480@60/75Hz, 800x600@60/75Hz, 1024x768@60/70/75Hz, 1280x960@60Hz, 1280x1024@60/70/75Hz, 1440x900/60Hz, 1680x1050@60Hz For HDMI & YPbPr- 480i, 480P, 720P, 1080i, 1080P @60Hz 576P, 576i, 720P, 1080P @50Hz
Display Colours	16.7M
Compatibility	VGA, XGA, SVGA, SXGA, WXGA+, WSXGA
HDCP Compatible	Yes
Input Signal	Analogue RGB, DVI-D, HDMI, YPbPR
Input Connector	D-Sub 15-pin, DVI-D 24-pin, HDMI, YPbPr
Power Source	Power Input: Universal 110~240VAC, 50/60Hz
Power Consumption	49 Watts (Max)
Plug & Play	DDC1/2B/CI
User Control	Auto Config, Volume/up, Volume/down, Menu, Source, Power
OSD Function	Brightness, Contrast, Audio Control, Focus, Clock, Input Select, H. Position, V. Position, OSD Setup, Language, normal Color, (Warm) Color, (Cool) Color, sRGB, RGB Color Temperature, Information, Reset, Exit
OSD Languages	English, Spanish, French, Portuguese, German, Russian, Italian, Simple Chinese
Speaker	3W x 2
Regulations	cUL, FCC, CE, EPA, TCO03, BSMI
Mechanical Features	Tilt, VESA 100mm Wall Mountable **
Dimensions(Monitor)	Monitor: 505(W)x211(D)x428.3(H) mm
Dimensions(Carton)	Carton: 590(W)x174(D)x520(H) mm
Weight(Net/Gross)	Net: 6.0 Kg ; Gross: 8.0 Kg
Container Loading	1040(40') / 416(20')

Note: Specifications are subject to change without notice.

*High-bandwidth Digital Content Protection: Enables viewing of High-Definition contents.

**Wall mount arm & bracket not included.

AOC[®]