



## FOVI series F22s



### TECHNICAL SPECIFICATIONS

<b>Model Name</b>	F22s
<b>Cabinet Colour</b>	Black
<b>Pixel / Dot Pitch</b>	0.248(H) × 0.248(V)mm
<b>Display Area</b>	477.5(H) × 268.5(V)mm
<b>VIS</b>	548mm
<b>Brightness</b>	300 cd/m <sup>2</sup>
<b>Contrast Ratio</b>	30000:1
<b>Response Time</b>	5ms
<b>Viewing Angle H / V</b>	170/160(CR ≥ 10)
<b>Scanning Frequency</b>	H:30~80KHz V:55~75Hz
<b>Pixel Frequency</b>	148MHz
<b>Maximum Resolution</b>	1920 x 1080@60Hz
<b>Recommended Resolution</b>	1920 x 1080@60Hz
<b>Display Colours</b>	16.7MHz
<b>Signal Inputs</b>	Analogue
<b>HDCP* Compatible</b>	No
<b>Input Connector</b>	15-pin D-Sub
<b>Power Supply</b>	110~240VAC, 50/60Hz
<b>Power Consumption</b>	On: <49W, Standby: < 1W
<b>Plug &amp; Play</b>	DDC 1/2B/CI or VESA DDC2B
<b>User Control</b>	Contrast/Left;ECO/up;Wide/right;Auto//Down;Power/Menu
<b>OSD Languages</b>	8 languages
<b>OSD Function</b>	Brightness, Contrast, Eco Mode, Gamma(1,2,3), DCR, Focus, Clock, H/V Position, Color Temperature (Cool,Warm,Normal,sRGB,User_R,G,B), Color Boost(Full Enhance, Nature Skin, Green Field, Sky Blue, Auto Detect, Demo) , Picture Boost(Frame Size, Brightness, Contrast, H/V Position, Bright Frame on/off), OSD Setup(H/V position, Timeout, Transparency, Language), Extra (Input Select, AUTO Config, Image Ratio, DDC/CI, Information), Reset, Exit
<b>Speaker</b>	No
<b>Regulations</b>	CUL,TUV/S,CCC,ROHS,ISO13406-2,CE,FCC,Windows Vista
<b>Dimensions (Monitor)</b>	525.5 x 379 x 80.9 mm
<b>Dimensions (Carton)</b>	590 x 451 x 162 mm
<b>Weight (Net / Gross)</b>	4.6Kg / 6.1Kg

Note: Specifications are subject to change without notice.

\*High-bandwidth Digital CONTENT Protection: Enables viewing of High-Definition contents.

Windows and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries.